


# DOBOT X-Trainer

AI Data Collection and  
Training Robotic System






# CONTENT

## Content

- 01 Introduction
- 02 Applications
- 03 Key Features

# 01 Introduction

ABOUT X-Trainer




# AGI (Artificial General Intelligence) Imitation Learning




Embodied intelligence is an important step towards Artificial General Intelligence (AGI), and **learning by imitation from demonstrations provided by humans** is a promising development approach for the future.


This **"behavior cloning"** approach can enable robots to learn a variety of basic skills, from simple pick-and-place operations to more fine-grained manipulations.



Experts Trajectory Learning



Pose-based Motion Learning




Locomotion Learning

# Pain Points for Imitation Learning


## High Cost of Data Collection Systems

Traditional data collection systems are expensive to build and difficult to set up, requiring high-end robots, high-precision sensors, complex environmental modeling, or intricate calibration systems.



## Inflexible Traditional Robotic Manipulators

For delicate tasks, such as threading flexible cables, the challenges for robots are enormous. They require high precision, high coordination, and complex real-time vision-based feedback systems, making it difficult to match the dexterity and flexibility of the human hand.



# Key Features




## X-Trainer



# X-Trainer Imitation Training

Vision-Language Models

X-Trainer : a




# X-Trainer Imitation Training



# 02 Application Scenarios

ABOUT X-Trainer Application



# X-Trainer-Application Scenarios



## AI Data Collection & Training

X-Trainer is capable of collecting diverse and contextualized data, such as images, videos, and positional information, to train embodied intelligence AI models. This enables the platform to meet the conventional data collection and training requirements of both academia and industry, such as simulating robots assisting with cooking at home or performing tasks like assembly and handling in industrial areas.



Wash dishes



Cook eggs




Pour water



Fold laundry


## Practical Projects & Competitions

University students can take advantage of the X-Trainer for various robotics and AI-related practical projects and competitions, while using it for creative experimentation or developing AI applications. The end result is enhanced practical skills and innovation mindset.



# 03 Key Features

ABOUT X-Trainer Features



## Rapid Training

Imitation learning data training is significantly shored by 70%, and routine scenario training (such as dish-washing or folding clothes) can be completed in just 2 hours.

**-70%**

Training Duration

**2 Hrs**


Routine Scenario Training



## Interference Resistance

During autonomous execution of scenario tasks, real-time disturbances can be quickly corrected. For example, the robot can recognize and remove stains that occur during the dish-washing process, resulting in a significant improvement in the robot's AI capabilities.

A certain degree of generalization



# X-Trainer-Features



## Industrial-Grade Precision

With Dobot Nova 2 Six-Axis Cobots, the X-Trainer platform achieves a high repeatability accuracy rate of up to 0.05mm.

**Nova 2**  
Robot Arms

**±0.05mm**  
Repeatability Accuracy






# X-Trainer-Safety Guarantee



## Master-Slave Safety Synchronization

Automatic disconnecting the master and slave hand upon power loss to prevent slave arm collision damage.



## Dual Emergency Stop Buttons

Equipped with dual emergency stop buttons, anywhere and anytime, pressing either one triggers a emergency stop to quickly prevent accidents.




## Slave Arm Collision Detection

Nova 2 6-Axis collaborative robot with built-in level 5 collision detection, ISO15066 safety certified, worry-free human-robot collaboration.



## Anti-Dropping Detection

**Master-hand abnormal drop detection**, effectively preventing operational errors from causing damage to the robot arm. Flexible EVA foam padding in the work space: Significantly reduces the risk of end-effector and robot arm damage.



# X-Trainer-High Performance Master-Hand



## Smooth Operation, Control as Needed

The **lightweight design** ensures that **the load on the user's hand during operation is less than 400g**, making it more comfortable and convenient to use. With high-performance servo motors and springs, it achieves higher motion capture accuracy, resulting in a more seamless remote control experience.



## Easy-to-Use Buttons

The master hand controller is equipped with **unlock and record buttons**. The unlock button allows for quick locking and unlocking of the master hand's posture, significantly reducing fatigue on the operator's hands. The record button enables convenient control of recording start or stop.



## Ergonomic Master-Hand

- Master-Slave Hand Configuration Consistency: Lossless scaling optimization for intuitive and dexterous operation.
- Symmetric Design of Operation Handle and Buttons: Suitable for both left and right hands, accommodating different user preferences.



## All-in-One Design

- Integrated Design of Master Hand: Integrated main controller in the base, resulting in a more compact form factor.
- One-Piece 3D Printed Linkage Components: Lighter and more streamlined robotic body.
- Hidden Wiring Design: Improved aesthetics and reduced interference, enhancing smooth operation.



# X-Trainer- Industrial-Grade Slave Hand



## Industrial-Grade Precision

Highly Precise Repeat Positioning Accuracy of  $\pm 0.05\text{mm}$ . Whether for delicate experimental operations or sensitive data collection, the robotic system can perform tasks with exceptional accuracy.



## Large Working Range

Nova2 reaches 625mm, and the combined dual-arm span can reach 1200mm. Coupled with 6-axis high flexibility, it can easily cover a broad workspace, effectively realizing data collection in different application scenarios.



## Large Payload, High Speed

- Nova2 has a max single-arm payload of 2Kg and a combined dual-arm payload of 3Kg, covering a wide range of applications.
- With a max speed of 1.6m/s, Nova2 boosts the efficiency of data collection, making it particularly suitable for rapid execution of data acquisition tasks.



## Collision Detection

Nova2 is equipped with 5-level collision detection functionality and is ISO15066 safety certified. It can immediately stop upon unexpected collisions, protecting the arm, surrounding equipment, and personnel, truly achieving human-robot collaboration.




# X-Trainer- Slave-Hand Gripper




## Large Gripper Stroke

Maximum gripper stroke of **95mm**: accommodating a wider range of operational needs from precise component assembly to handling larger items, the robotic system can easily handle diverse tasks.



## High Gripping Force

High gripping force **up to 15N**, enabling more stable grasping operations. Suitable for handling small everyday items as well as precision lab and industrial gripping tasks.



## Parallel Dual Slider Design

Enables rapid and precise motion response during the gripper opening and closing process, achieving secure grasping. Enhances the durability and reliability of the gripper, meeting the requirements for long-term, high-intensity data acquisition tasks.



## Lightweight Design

Lightweight design, monolithic 3d-printed structure - reduces the load on the entire robotic arm, effectively enhancing agility and precision of operation.



# X-Trainer-3D In-depth Camera



## Sub-millimeter Level Precision

The precise environmental data provides a solid foundation for machine learning and imitation learning, enabling the system to more accurately interpret the operational environment, thereby optimizing the training effectiveness of neural network models.



## Multi-Angle Adjustable

The camera is capable of **pitch, forward/backward** adjustments. the camera angle can be adjusted according to the specific task requirements, providing great flexibility for use in different scenarios.



## Wide Field of View

The wide field of view reduces the need for frequent angle adjustments, especially in complex or space-constrained environments. this allows capturing multi-angle data in a single shot, significantly improving the efficiency and practical utility of data collection.



## 3-view Camera Design for Richer Data

With three depth cameras, multi-angle observation and recording, the system can capture abundant visual information. this allows the system to better understand the environment and objects, and more quickly compute the optimal robot path and operation strategy.



# X-Trainer- Multi-Fuction Base



## Full Base, Easy to Deploy

The main and auxiliary robotic arms, as well as the control cabinet, are all integrated into a single base unit - greatly enhancing the flexibility and ease of use of the device. This allows deployment and usage across diverse environments, meeting the needs of various applications.



## Lightweight Base, Convenient to Remove

The lightweight design reduces the weight by 70%, with a separate control cabinet, and 4 convenient handles, enabling flexible deployment and easy transportation. 6 fixed feet are included to enhance the stability of the device when deployed on a desktop.



## Large Operational Space with Brilliant Expandability

The master hand and slave hand can have their **installation positions freely adjusted based on the requirements**, to adapt to different application scenarios.

Nova 2 slave hand can be rotated 90 degrees for installation, enabling it to perform tasks that extend beyond the platform.



# X-Trainer- Secondary Development



## Full SDK for data collection, training, and inference

Provides complete development scripts covering the entire workflow, **from data collection to autonomous inference**. Includes detailed user manuals to systematically guide users from the basics, greatly simplifying the learning and application process, and accelerating the transition from theory to practice.

## Open API Interfaces

The system is equipped with a data training SDK, offering open API interfaces. It supports exporting data in specialized formats, enabling direct integration with custom AI neural network models. It allows for multi-model large-model training and research, facilitating various research projects.

**The API interfaces include: reading/controlling the joint angles of the main arm, reading/controlling the joint angles and Cartesian coordinates of the slave arm, controlling the gripper open/close degree, and capturing RGB camera images.**

```
dobot.py x dobot_api.py dobot_gripper_new.py launch_camera_nodes.py
346 pos_quat = np.zeros(7)
347 gripper_pos = np.array([joints[-1]])
348 return {
349     "joint_positions": joints,
350     "joint_velocities": joints,
351     "ee_pos_quat": pos_quat,
352     "gripper_position": gripper_pos,
353 }
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
```

```
# set torque
right_agent.set_torque(True) # 将右手臂设置为力矩模型; True改为False即为解除力矩
left_agent.set_torque(True) # 将左手臂设置为力矩模型; True改为False即为解除力矩

while 1:
    # 左、右手关节角度
    print(left_agent.act({}), right_agent.act({})) # joints
    # 左、右手末端按键状态
    print(left_agent.get_keys(), right_agent.get_keys()) # button status
```

# Thank you.



 [www.dobot-robots.com](http://www.dobot-robots.com)

 [sales@dobot-robots.com](mailto:sales@dobot-robots.com)

 [www.linkedin.com/company/dobot-usa/](http://www.linkedin.com/company/dobot-usa/)

 [linkedin.com/company/dobotrobotics/](http://linkedin.com/company/dobotrobotics/)

 [youtube.com/@DobotRobotics](http://youtube.com/@DobotRobotics)